



**Product** Catalogue

**2025**





**Awic®**  
we build future



# EPOXY GROUT

## 3-Part

3 Part Epoxy Based  
Tiles Joint Filler



For Internal Floor & Wall,  
Swimming Pool



Crack Free



Stain-free &  
Chemical Resistant.



Waterproof



Available in Different  
Colours



Low VOC

### Description

AWIC 3-Part Epoxy Grout is a premium-quality, high-performance grout designed for durability and long-lasting performance. Ideal for a wide range of applications, this epoxy grout combines strength, aesthetic appeal, and easy maintenance, making it a preferred choice for both residential and commercial installations.

### Conclusion

AWIC 3-Part Epoxy Grout offers unparalleled customization with 23 shades and 3 different sparkles to enhance your space. Whether you're designing a classic or contemporary look, our grout delivers not only in terms of beauty but also in durability and ease of use. Transform your space with the perfect grout that fits your style and exceeds your expectations.

### Area of Application

• Residential Kitchens and Bathrooms • Commercial Spaces • Pools & Spas • Outdoor Environments • High-Traffic Areas

### Technical Information

#### Application Properties

Sr.No.	Testing Parameter	Test Result
1	Joint Width	15 mm
2	Pot Life	50 min
3	Time to Foot Traffic	24 hrs
4	Time to Heavy Traffic	48 hrs
5	Specific Gravity	1.6 to 1.7 kg/ltr
6	Shrinkage	No Shrinkage
7	Water Cleaning	< 60 min>
8	Setting Time	3 hrs
9	Sag	No sagging
10	Compressive Strength	> 6500 PSI
11	Tensile Strength	> 1300 PSI

### Application Preparation

- Clean joints and surface with brush and scrub pad.
- Mix Part A & Part B in a bucket thoroughly and slowly add Part C (Filler Powder) to make a homogenous mixture.
- Apply mixture with applicator blade.
- Wait for 60-90 min for joints to be set.
- Clean up spillage material with shampoo water and sponge.
- Do not disturb applied area and allow it to dry for 24 hrs.
- Surface is now shiny and ultra durable ready to use.

### Safety

Always wear hand gloves while using  
AW-101 EPOXY GROUT.

### Self Life

Shelf life is 3 year on the date of manufacturing in unopened  
condition. Store in a cool and dry place.



Morbi, Gujarat-363642.

Mail us on : [awicind@gmail.com](mailto:awicind@gmail.com)

Follow us :



MADE IN INDIA

